

SMYRNA, TENNESSEE

AL-895 (FAA)

23054

LOC I-MQY <u>111.1</u>	APP CRS 321°	Rwy Idg 8038 TDZE 518 Apt Elev 543
----------------------------------	------------------------	---

ILS or LOC/DME RWY 32
SMYRNA (MQY)


▼ DME from BNA VORTAC, simultaneous reception of I-MQY and BNA DME required. For inop MALSR, increase S-LOC 32 Cats C/D visibility to 1 mile. For inop MALSR when using Nashville Intl altimeter setting, increase S-LOC 32 Cats C/D visibility $\frac{1}{2}$ mile. When local altimeter setting not received, use Nashville Intl altimeter setting and increase all DA to 749 feet and all MDA 40 feet; increase S-LOC 32 Cats C/D visibility $\frac{1}{8}$ mile and increase Circling 40 feet C/D visibility $\frac{1}{4}$ mile. VDP NA when using Nashville Intl altimeter setting.

MALS R



MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 on heading 090° and BNA VORTAC R-127 to CUYAG INT/ BNA VORTAC 18.6 DME and hold.

AWOS-3PT 119.125	NASHVILLE APP CON 118.4 360.7	SMYRNA TOWER ★ 118.5 (CTAF) 0 233.1	GND CON 121.4	CLNC DEL 121.4	CLNC DEL 121.7 (When twr closed)	UNICOM 122.95
---------------------	----------------------------------	--	------------------	-------------------	--	------------------

[illegible]

SMYRNA, TENNESSEE

Amdt 6A 20AUG15

SMYRNA (MOY)

36°01'N-86°31'W

ILS or LOC/DME RWY 32