RNAV (GPS) RWY 31

DUBUQUE RGNL (DBQ)

WAAS	APP CRS	Rwy Idg	6502
CH 69400	312°	TDZE	1062
W31A		Apt Elev	1077

RNP APCH - GPS.

For inop ALS, increase LPV all Cats visibility to 1½ SM and LNAV Cats A and B visibility to 1 SM. Baro-VNAV NA when using Monticello altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 46°C. VDP NA when using Monticello altimeter setting. If local altimeter setting not received, use Monticello altimeter setting and increase all DAs/MDAs 100 feet.

MALSR

MISSED APPROACH: Climb to 2800 direct HULOT and hold.

ATIS	CHICAGO CENTER	DUBUQUE TOWER★	GND CON	UNICOM
127.25	133.95 281.4	119.5 (CTAF) L 254.4	121.8	122.95



ELEV 1077 D TDZE 1062



REIL Rwy 18 L
HIRL Rwys 13-31 and 18-36 L



CATEGORY	A	B	C	D
LPV DA	1481-1 419 (500-1)			
LNAV/VNAV DA	1603-1½ 541 (600-1½)			
LNAV MDA	1540-¾ 478 (500-¾)			1540-1 478 (500-1)
C CIRCLING	1620-2 543 (600-2)			1800-2¼ 723 (800-2¼)

NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024