WAAS	APP CRS	Rwy Idg	7302
CH 86617	135°	TDZE	803
W14A		Apt Elev	808

RNAV (GPS) RWY 14

SOUTHERN WISCONSIN RGNL (JVL)

RNP APCH-GPS.

T A Circling Rwy 18 NA at night. Baro-VNAV NA when using Rockford altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C. VDP NA when using Rockford altimeter setting. When local altimeter setting not received, use Rockford altimeter setting and increase LPV DA to 1072 feet, LNAV/VNAV DA to 1291 feet, and all MDAs 80 feet; increase LPV all Cats visibility ⅛ SM, LNAV/VNAV all Cats visibility ¼ SM, LNAV Cat C/D visibility ¼ SM, and Circling Cat C/D visibility ¼ SM.

MISSED APPROACH: Climb to 3100 direct TIRRO and hold.

ATIS	ROCKFORD APP CON	JANESVILLE TOWER ★	GND CON	CLNC DEL	UNICOM
128.25	121.0 327.0	118.8 (CTAF) L 225.4	121.65	121.65	122.95



ELEV 808 D TDZE 803



REIL Rwys 14 and 22 L
MIRL Rwy 18-36 L
HIRL Rwys 4-22 and 14-32 L



CATEGORY	A	B	C	D
LPV DA	1003-¾ 200 (200-¾)			
LNAV/VNAV DA	1222-1⅛ 419 (500-1⅛)			
LNAV MDA	1280-1 477 (500-1)		1280-1⅜ 477 (500-1⅜)	1280-1⅜ 477 (500-1⅜)
CIRCLING	1280-1 472 (500-1)	1320-1 512 (600-1)	1420-1¾ 612 (700-1¾)	1460-2 652 (700-2)

EC-3, 18 APR 2024 to 16 MAY 2024
EC-3, 18 APR 2024 to 16 MAY 2024