WAAS	APP CRS		
CH **66010**	**059°**	Rwy Idg	**7006**
W06A		TDZE	**94**
		Apt Elev	**99**

RNAV (GPS) RWY 6
LONG ISLAND MAC ARTHUR (ISP)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C (7°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP and Baro-VNAV NA when using Shirley altimeter setting. When local altimeter setting not received, use Shirley altimeter setting and increase all DA 28 feet and all MDA 40 feet, increase LNAV/VNAV all Cats visibility to RVR 3000 and LNAV Cat C and D visibility to 4500. Increase Circling Cat C and D visibility ¼ mile. For inoperative MALSR, increase LNAV/VNAV all Cats visibility to RVR 4500 and LNAV Cat C and D to RVR 6000. For inoperative MALSR when using Shirley altimeter setting increase LNAV/VNAV all Cats visibility to RVR 5000. **RVR 1800 authorized with use of FD or AP or HUD to DA, NA when using Shirley altimeter setting.

MALSR

MISSED APPROACH: Climb to 600 then climbing right turn to 2000 direct CCC VOR/DME and hold.

ATIS	NEW YORK APP CON	LONG ISLAND TOWER*	GND CON	CLNC DEL	UNICOM
120.725	**120.05 343.75**	**119.3** (CTAF) L **335.5**	**135.3**	**121.85**	**122.95**



ELEV 99	D	TDZE 94





CATEGORY	A	B	C	D
LPV DA		**294/24	200 (200-½)	
LNAV/VNAV DA		385/24	291 (300-½)	
LNAV MDA	500/24	406 (500-½)	500/40	406 (500-¾)
C CIRCLING	600-1 501 (600-1)	660-1 561 (600-1)	660-1½ 561 (600-1½)	960-2¾ 861 (900-2¾)

MIRL Rwy 15R-33L L
HIRL Rwy 6-24 L

NE-2, 18 APR 2024 to 16 MAY 2024
NE-2, 18 APR 2024 to 16 MAY 2024