



WAAS CH 97530 W24A	APP CRS 239°	Rwy Idg 6006 TDZE 193 Apt Elev 213
--	------------------------	---

RNAV (GPS) Z RWY 24
TRENTON MERCER (TTN)

⚠ Baro-VNAV NA when using Northeast Philadelphia altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C (8°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Northeast Philadelphia altimeter setting: increase LPV DA to 626 feet and LNAV/VNAV DA to 677 feet and all visibilities ½ mile; increase all MDA 60 feet and LNAV Cats C and D visibilities ⅓ mile and Circling visibility Cat C ¼ mile. VDP NA with Northeast Philadelphia altimeter setting. Helicopter visibility reduction below ⅓ SM NA. Night Landing: Rwy 34 operational VGSI required, remain on or above VGSI glidepath until threshold.

MISSED APPROACH:
Climb to 2700 direct ZUBAX and hold.

ATIS 126.775	PHILADELPHIA APP CON 123.8 291.7	TRENTON TOWER ★ 120.7 (CTAF) 0 257.8	GND CON 121.9 257.8	CLNC DEL 121.9 257.8	UNICOM 122.95
------------------------	--	--	-------------------------------	--------------------------------	-------------------------



ELEV 213	D	TDZE 193
2700 ZUBAX		
VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 42).		
4 NM Holding Pattern		
BIRKE		
059° 2600		
239°		
1900		
239°		
1020		
1900		
239°		
2600		
GP 3.00° TCH 55		
1.2 NM 1.3 NM 2.7 NM 6.0 NM		
CATEGORY	A	B C D
LPV DA	580-1¼	387 (400-1¼)
LNAV/VNAV DA	631-1½	438 (500-1½)
LNAV MDA	620-1 428 (500-1)	620-1¼ 428 (500-1¼)
CIRCLING	680-1 467 (500-1)	760-1½ 547 (600-1½) 960-2½ 747 (800-2½)