RNAV (GPS) RWY 24

CUYAHOGA COUNTY (CGF)

WAAS CH 42528 W24A	APP CRS 238°	Rwy Idg 5000 TDZE 873 Apt Elev 876

RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 38°C . For inop ALS increase LNAV/VNAV visibility all Cats to ⅞ SM, LNAV Cat C, D to 1⅛ SM.

MALSR

MISSED APPROACH: Climb to 2500 then climbing left turn to 3000 direct ZUPKO and hold.

D-ATIS	CLEVELAND APP CON	COUNTY TOWER★	GND CON	CLNC DEL
119.95	125.35 346.325	118.5 (CTAF) L	121.85	121.85 (when tower closed)





CATEGORY	A	B	C	D
LPV DA	1073-½ 200 (200-½)			
LNAV/VNAV DA	1178-½ 305 (400-½)			
LNAV MDA	1280-½ 407 (500-½)		1280-¾ 407 (500-¾)	
C CIRCLING	1400-1 524 (600-1)	1500-1 624 (700-1)	1560-2 684 (700-1)	1620-2½ 744 (800-2½)

ELEV 876 D TDZE 873



REIL Rwy 6 L
HIRL Rwy 6-24 L

EC-2, 18 APR 2024 to 16 MAY 2024
EC-2, 18 APR 2024 to 16 MAY 2024