RNAV (GPS) RWY 5

GROTON-NEW LONDON (GON)

WAAS	APP CRS	Rwy Idg	5000
CH 45521	048°	TDZE	8
W05A		Apt Elev	9

RNP APCH - GPS.

Circling Rwy 15 NA at night. For uncompensated Baro-VNAV systems, procedure NA below -15°C or above 54°C. For inop ALS, increase LPV all Cats visibility to RVR 4500 and LNAV Cats visibility C/D to 1⅜.

MALSR

MISSED APPROACH: Climb to 2100 direct BRRET and on track 068° to BABET and hold, continue climb-in-hold to 2100.

ATIS	PROVIDENCE APP CON ★	GROTON TOWER ★	GND CON	CLNC DEL	CLNC DEL
127.0	125.75 319.2	125.6 (CTAF) 236.775	121.65 236.775	119.85 (when twr closed)	121.65



ELEV	9	D	TDZE	8



CATEGORY	A	B	C	D
LPV DA	292/24 284 (300-½)			
LNAV/ VNAV DA	533/55 525 (600-1)			
LNAV MDA	500/24 492 (500-½)		500/50 492 (500-1)	
CIRCLING	580-1 571 (600-1)	620-1 611 (700-1)	700-2 691 (700-2)	840-2¾ 831 (900-2¾)



REIL Rwys 23 and 33
HIRL Rwys 5-23 and 15-33 (L)

NE-1, 18 APR 2024 to 16 MAY 2024
NE-1, 18 APR 2024 to 16 MAY 2024