


WAAS CH 90319 W18A	APP CRS 184°	Rwy Idg TDZE Apt Elev 6557 80 90
--	------------------------	--

RNAV (GPS) RWY 18
OCALA INTL-JIM TAYLOR FLD (OCF)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Gainesville altimeter setting and increase LPV DA to 361 feet, increase LNAV/VNAV DA to 595 feet and all MDA 100 feet; increase LPV and LNAV/VNAV all Cats and LNAV Cats C/D visibility ¼ SM; increase Circling Cat C visibility ½ SM, Cat D ¼ SM. Baro-VNAV and VDP NA when using Gainesville altimeter setting.

MISSED APPROACH:
Climb to 2000 direct
TALZA and hold.

ATIS 128.125	JACKSONVILLE APP CON 118.6 251.15	OCALA TOWER ★ 119.25 (CTAF) 0	GND CON 121.4
------------------------	---	---	-------------------------



4 NM Holding Pattern				VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 45).		2000	TALZA
2100 ← 004° → 184° → 1700				LUGGY		CUMIB 1.8 NM to RW18	*1.1 NM to RW18
GP 3.00° TCH 52				*700		*RNAV only.	
6.1 NM				3.1 NM		0.7	
CATEGORY A				CATEGORY B		CATEGORY C	
LPV DA 280-¾				200 (200-¾)			
LNAV/VNAV DA 514-1½				434 (500-1½)			
LNAV MDA 480-1				400 (400-1)		480-1¼	
CIRCLING 600-1				510 (600-1)		760-1¾	
						670 (700-1¾)	
						920-2¾	
						830 (900-2¾)	

