

TAKEOFF MINIMUMS

Rwy 7: Standard with a minimum climb of 500' per NM to 580. Rwy 25: Standard with a minimum climb of 500' per NM to 580.

NOTE: RNAV 1.

NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

NOTE: SLI turbojet/turboprop departures expect vectors/direct to SLI/V64/TRM.

NOTE: SLI prop departures expect left turn/vectors to LIMBO SLI/V64. NOTE: LAX departures expect left turn/vectors/direct to LAX/LAX310R. NOTE: EXERT departures expect vectors/direct to EXERT/V25/V27.

NOTE: VTU departures expect vectors/direct to VTU.

NOTE: Chart not to scale.

V

SW-3,

18 APR 2024 to

16 MAY 2024

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 7: Climb on heading 073° to 580, then turn right direct to cross SPACX at 3000 then on track 200. Thence

TAKEOFF RUNWAY 25: Climb on heading 253° to intercept course 200° to cross SPACX at 3000 then on track 200°. Thence

. . . . on assigned course/route. Maintain ATC assigned altitude. Expect filed altitude 5 minutes after departure.