WAAS CH 56223 W03A | APP CRS 028° | Rwy Idg 8003 TDZE 888 Apt Elev 918

RNAV (GPS) RWY 3

APPLETON INTL (ATW)

T A Baro-VNAV NA below -16°C (4°F). DME/DME RNP-0.3 NA. When local altimeter setting not received use Green Bay-Austin Straubel Intl altimeter setting and increase all DAs/MDAs 100 feet. Baro/VNAV and VDP NA when using Green Bay-Austin Straubel Intl altimeter setting. For inoperative MALSR increase LPV visibility to RVR 4000 all Cats.

MALSR

MISSED APPROACH: Climb to 2700 direct ASIGE and hold.

ATIS	GREEN BAY APP CON★	APPLETON TOWER★	GND CON	UNICOM
127.15	126.3 338.2	119.6 (CTAF)	121.7	122.95





CATEGORY	A	B	C	D
LPV DA	1138/24 250 (300-½)			
LNAV/VNAV DA	1232/40 344 (400-¾)			
LNAV MDA	1400/24 512 (500-½)		1400/50 512 (500-1)	1400/60 512 (500-1¼)
C CIRCLING	1400-1 482 (500-1)		1400-1½ 482 (500-1½)	1480-2 562 (600-2)

ELEV 918 D TDZE 888



REIL Rwys 12 and 21 L
HIRL Rwys 12-30 and 3-21 L

EC-3, 18 APR 2024 to 16 MAY 2024
EC-3, 18 APR 2024 to 16 MAY 2024