VOR/DME SPW	APP CRS	Rwy Idg	5511
115.15	292°	TDZE	1338
Chan 98 (Y)		Apt Elev	1339

VOR RWY 30
SPENCER MUNI (SPW)

DME required.

VDP NA when using Estherville altimeter setting.
When local altimeter setting not received, use Estherville altimeter setting and increase all MDA 60 feet and increase S-30 Cat C/D visibility ½ SM and Circling Cat C/D visibility ¼ SM.

MISSED APPROACH: Climb to 3000, then left turn direct SPW VOR/DME, then on SPW VOR/DME R-112 to ZUNMU/SPW 5.3 DME and hold.

ASOS	MINNEAPOLIS CENTER	UNICOM
126.625	127.75 257.7	123.0 (CTAF) L



ELEV 1339 TDZE 1338



REIL Rwys 18, 30 and 36 L
MIRL Rwys 12-30 and 18-36 L



CATEGORY	A	B	C	D
S-30	2080-1 742 (800-1)	2080-1¼ 742 (800-1¼)	2080-2 742 (800-2)	
C CIRCLING	2080-1 741 (800-1)	2080-1¼ 741 (800-1¼)	2100-2¼ 761 (800-2¼)	2100-2½ 761 (800-2½)

NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024