# RNAV (GPS) RWY 12R

## ST LOUIS DOWNTOWN (CPS)

| APP CRS | Rwy Idg | 7002 |
|---|---|---|
| 107° | TDZE | 413 |
| | Apt Elev | 413 |

RNP APCH - GPS.

When local altimeter setting not received, use St Louis Lambert Intl altimeter setting and increase all MDAs 80 feet; increase LNAV Cats B/C/D and Circling Cat C visibility ¼ SM. Circling Rwy 5 NA at night. Rwy 12R helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 2200 direct JIXAB and right turn on 125° track to LICKO and hold.

| ATIS | ST LOUIS APP CON | DOWNTOWN TOWER ★ | GND CON | CLNC DEL | CLNC DEL (when twr closed) | UNICOM |
|---|---|---|---|---|---|---|
| 121.45 | 123.7 371.875 | 119.925 (CTAF) L 379.3 | 121.8 | 118.275 | 121.8 | 122.95 |










| CATEGORY | A | B | C | D |
|---|---|---|---|---|
| LNAV MDA | 1140-1 727 (800-1) | | 1140-2 727 (800-2) | 1140-2¼ 727 (800-2¼) |
| CIRCLING | 1140-1 727 (800-1) | | 1240-2½ 827 (900-2½) | 1380-3 967 (1000-3) |

HIRL Rwy 12R-30L
REIL Rwys 12L and 12R
REIL Rwy 30R L
MIRL Rwys 5-23 and 12L-30R



EC-3, 18 APR 2024 to 16 MAY 2024
EC-3, 18 APR 2024 to 16 MAY 2024