

WAAS
CH **40235**
W28A

APP CRS
276°

Rwy Idg
TDZE
Apt Elev

3181
308
308

RNAV (GPS) RWY 28

HERITAGE FLD (PTW)

⚠

Circling NA south of Rwy 10-28. DME/DME RNP-0.3 NA. VDP and Baro-VNAV NA when using Wings Fld altimeter setting. When local altimeter setting not received, use Wings Fld altimeter setting and increase all DA 35 feet and all MDA 40 feet, increase LPV all Cats visibilities 1/8 mile. Helicopter visibility reduction below 3/4 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F).

MISSED APPROACH:
Climb to 2600 direct EZABO and hold.

ASOS 119.425	PHILADELPHIA APP CON 126.85 263.125	CLNC DEL 118.55	UNICOM 122.7 (CTAF) 0
------------------------	---	---------------------------	---------------------------------

The main chart displays the RNAV (GPS) RWY 28 approach. Key features include:

- MSA RW28 25 NM** circle with a **2900** ft MSL.
- Elevations:** 1549, 1360, 1265, 1044, 1180±.
- Navigation Aids:** SPUDS (2400 ft, 149°), EZABO (276°), IZIWA (276°), BIDDU (276°), AWISA (2200 ft), MAZIE (2200 ft).
- Altitudes:** 2200 ft at various points, 276° heading.
- Distances:** 1.4 NM, 3.5 NM, 7.1 NM.

ELEV 308

TDZE 308

2600

EZABO

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 45).

*LNAV only

RW28

BIDDU 2200

IZIWA 2200

GP 3.55°
TCH 60

1.4 NM

3.5 NM

7.1 NM

CATEGORY	A	B	C	D
LPV DA	652-1	344 (400-1)	NA	
LNAV/VNAV DA	779-1 3/8	471 (500-1 3/8)	NA	
LNAV MDA	820-1	512 (600-1)	NA	
CIRCLING	940-1	632 (700-1)	NA	

POTTSTOWN, PENNSYLVANIA
Orig-B 18AUG16

40°14'N-75°33'W

HERITAGE FLD (PTW)
RNAV (GPS) RWY 28