

|                       |             |          |      |
|-----------------------|-------------|----------|------|
| LOC/DME I- <u>UZA</u> | APP CRS     | Rwy Idg  | 5500 |
| <u>108.5</u>          | <u>016°</u> | TDZE     | 666  |
| Chan <u>22</u>        |             | Apt Elev | 666  |

ILS Y or LOC Y RWY 2

ROCK HILL/YORK COUNTY/BRYANT FLD (UZA)

**V** ADF or DME required. VDP NA with Charlotte/Douglas Intl altimeter setting. When local altimeter setting not received, use Charlotte/Douglas Intl altimeter setting and increase all DA 45 feet and all MDA 60 feet. Increase S-LOC 2 Cat C/D visibility 1/4 mile. For inop MALSR, increase S-LOC 2 Cat C/D visibility to 1 1/8 mile. For inop MALSR, when using Charlotte/Douglas Intl altimeter setting, increase S-LOC 2 Cat C/D visibility to 1 1/8 mile.

**MAISR**

**MISSED APPROACH:** Climb to 1500 then climbing left turn to 3000 on heading 174° and CLT VOR/DME R-203 to CONEL/I-UZA 12.7 DME/RADAR and hold.

|                        |                                          |                       |                                  |
|------------------------|------------------------------------------|-----------------------|----------------------------------|
| ASOS<br><b>120.775</b> | CHARLOTTE APP CON<br><b>120.05 307.8</b> | GCO<br><b>121.725</b> | UNICOM<br><b>123.05 (CTAF) 0</b> |
|------------------------|------------------------------------------|-----------------------|----------------------------------|

