

WAAS
CH **82021**
W25A

APP CRS
249°

Rwy Idg
TDZE **1038**
Apt Elev **1062**

RNAV (GPS) RWY 25

GWINNETT COUNTY/BRISCOE FLD (LZU)

RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. For inop ALS, increase LNAV Cat C/D visibility to 1½ SM.

MALS R

MISSED APPROACH: Climb to 1600 then climbing left turn to 3000 direct JOKLI and hold.

ATIS
132.275

ATLANTA APP CON
126.975 239.275

GWINNETT TOWER ★
124.1 (CTAF) **0**

GND CON
121.8

CLNC DEL
121.8

CLNC DEL
134.0
(When twr closed)

UNICOM
123.05

The main approach chart shows the RNAV (GPS) RWY 25 procedure. It begins with a 30 NM to JOKLI holding pattern with altitudes of 4800, 3000, and 4700 feet. The initial approach is 159° for 4 NM to JOKLI, then 339° for 4 NM to JOKLI. From JOKLI, the approach is 249° for 6.6 NM (2800 feet) to the ATUDE fix. From ATUDE, the approach is 249° for 1.4 NM to RW25. A missed approach procedure is shown: climb to 1600 feet, then 3000 feet, and hold at JOKLI. The chart also shows various altitudes (1578, 1276, 1219±, 1298, 1370±, 1379, 1615, 2062, 2549, 2654) and distances (4 NM, 6.6 NM, 1.4 NM, 4 NM, 6.6 NM, 30 NM).

ELEV 1062

TDZE 1038

249° to RW25

6001 X.100

0.5% UP

TWR

1600

3000

JOKLI

*LNAV only.

ATUDE

2800

249°

6000

3000

GP 3.00°

TCH 48

1.4 NM

4 NM

6.6 NM

CATEGORY	A	B	C	D
LPV DA		1238-½	200 (200-½)	
LNAV/VNAV DA		1477-¾	439 (500-¾)	
LNAV MDA	1520-½	482 (500-½)	1520-1	482 (500-1)
CIRCLING	1640-1	578 (600-1)	1680-1¾ 618 (700-1¾)	1700-2 638 (700-2)

LAWRENCEVILLE, GEORGIA

Amdt 1 17JUN21

GWINNETT COUNTY/BRISCOE FLD (LZU)

33°59'N-83°58'W

RNAV (GPS) RWY 25