RNAV (GPS) RWY 32

WEBSTER CITY MUNI (EBS)

WAAS	APP CRS	Rwy Idg	3851
CH 90516	321°	TDZE	1122
W32A		Apt Elev	1122

T A For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Clarion altimeter setting and increase all DA 49 feet and all MDA 60 feet. Baro-VNAV and VDP NA when using Clarion altimeter setting. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 3000 direct HOGOD and hold.

AWOS-3	MINNEAPOLIS CENTER	UNICOM
127.825	134.0 288.3	122.8 (CTAF) L



ELEV 1122 TDZE 1122



MIRL Rwy 14-32 L
REIL Rwys 14 and 32 L



CATEGORY	A	B	C	D
LPV DA	1372-1 250 (300-1)		NA	
LNAV/VNAV DA	1372-1 250 (300-1)		NA	
LNAV MDA	1460-1 338 (400-1)		NA	
C CIRCLING	1600-1 478 (500-1)		NA	

NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024