

WAAS CH 65728 W17A	APP CRS 168°	Rwy Idg TDZE 25 Apt Elev 27
--	------------------------	---

RNAV (GPS) Y RWY 17R

SACRAMENTO INTL (SMF')

RNP APCH - GPS.

▼

Circling NA east of Rwy 17R-35L. Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500 and LNAV all Cats visibility to RVR 5500.

ALS-F-2

ⓘ

MISSED APPROACH: Climb to 500 then climbing right turn to 2000 direct GRIME and hold.

D-ATIS 126.75	NORCAL APP CON 125.4 259.1 (W-NE) 125.25 257.9 (SW) 127.4 317.5 (E-SE)	CAPITOL TOWER 125.7 256.7	GND CON 121.7 256.7	CLNC DEL 121.1 256.7	CPDLC
-------------------------	---	-------------------------------------	-------------------------------	--------------------------------	-------

ELEV 27	D	TDZE 25
---------	----------	---------

TDZ/CL Rwy 17L and 17R
HIRL Rwy 17R-35L and 17L-35R

500	2000	GRIME	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).	
	1 NM to RWY17R	AMUNE 3.2 NM to RWY17R	JARNU 1800	
	1 NM	2.3 NM	2.2 NM	
112 ±	150	107	150	
35L	35R			
168°	168°	168°	168°	
1800	1800	1800	1800	
GP 3.00°	TCH 57			
CATEGORY	A	B	C	D
LPV DA	225/18	200 (200-½)		
LNAV/VNAV DA	323/24	298 (300-½)		
LNAV MDA	400/24	375 (400-½)	400/35	375 (400-¾)
CIRCLING	440-1 413 (500-1)	480-1 453 (500-1)	480-1½ 453 (500-1½)	580-2 553 (600-2)

SACRAMENTO, CALIFORNIA

Amtd 2D 23FEB23

38°42'N-121°35'W

SACRAMENTO INTL (SMF')

RNAV (GPS) Y RWY 17R