WAAS	APP CRS	Rwy Idg	5010
CH 82704	348°	TDZE	951
W35A		Apt Elev	951

RNAV (GPS) RWY 35

JACKSON COUNTY (JCA)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Circling NA for Cat D west of Rwy 17-35. Baro-VNAV and VDP NA when using Winder altimeter setting. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Winder altimeter setting: increase LPV DA to 1232 feet and LNAV/VNAV DA to 1241 feet and all MDA 40 feet; increase LPV visibility all Cats, LNAV/VNAV visibility all Cats, and LNAV Cat C/D visibility ⅛ mile; increase Circling Cat C visibility ¼ mile.

MISSED APPROACH: Climb to 3700 direct CERTA and hold.

AWOS-3PT	ATLANTA APP CON *	UNICOM
118.125	132.475 291.1	122.975 (CTAF) L







CATEGORY	A	B	C	D
LPV DA	1201-¾ 250 (300-¾)			
LNAV/VNAV DA	1210-¾ 259 (300-¾)			
LNAV MDA	1340-1 389 (400-1)		1340-1⅛ 389 (400-1⅛)	
C CIRCLING	1440-1 489 (500-1)		1520-1½ 569 (600-1½)	1520-2 569 (600-2)

SE-4, 18 APR 2024 to 16 MAY 2024
SE-4, 18 APR 2024 to 16 MAY 2024