# RNAV (GPS) RWY 28

GENESEE COUNTY (GVQ)

| WAAS CH 86311 W28A | APP CRS 282° | Rwy Idg 5499<br>TDZE 911<br>Apt Elev 914 |
|---|---|---|

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 46°C (114°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Rochester altimeter setting: increase LPV DA to 1263 feet and visibility ¼ SM all Cats; increase LNAV/VNAV DA to 1466 feet and visibility ½ SM all Cats; increase all MDA 120 feet and visibility LNAV Cat C ¼ SM and Circling Cats C and D ½ SM. Baro-VNAV and VDP NA when using Rochester altimeter setting. For inop MALSR increase LNAV Cat D visibility to 1¼ mile. For inop MALSR, when using Rochester altimeter setting increase LPV visibility all Cats to 1¼ mile.

MALSR

MISSED APPROACH: Climb to 3300 direct WAVRU and left turn via 162° track to YAVUD and left turn via 063° track to POCZI and hold.

| AWOS-3PT | ROCHESTER APP CON | CLNC DEL | UNICOM |
|---|---|---|---|
| 127.525 | 123.7 322.3 | 121.8 | 122.7 (CTAF) L |




2062

| ELEV 914 | TDZE 911 |
|---|---|




REIL Rwy 10 L
HIRL Rwy 10-28 L




| CATEGORY | A | B | C | D |
|---|---|---|---|---|
| LPV DA | 1161-½ 250 (300-½) | | | |
| LNAV/VNAV DA | 1364-1 453 (500-1) | | | |
| LNAV MDA | 1260-½ 349 (400-½) | | | 1260-1 349 (400-1) |
| CIRCLING | 1380-1 466 (500-1) | | 1720-2¼ 806 (900-2¼) | 1720-2½ 806 (900-2½) |



NE-2, 18 APR 2024 to 16 MAY 2024
NE-2, 18 APR 2024 to 16 MAY 2024