RNAV (GPS) RWY 4

EASTON/NEWNAM FLD (ESN)

WAAS CH 86905 W04A	APP CRS 040°	Rwy Idg 4775 TDZE 58 Apt Elev 72

RNP APCH - GPS.

When local altimeter setting not received, use Cambridge altimeter setting; increase LPV DA to 303 feet, LNAV/VNAV DA to 670 feet and visibility ⅛ SM; increase all MDAs 60 feet and visibility LNAV Cat C/D and Circling Cat C ⅛ SM, and Circling Cat D ¼ SM. VDP and Baro-VNAV NA when using Cambridge altimeter setting. Circling Rwy 15, 33 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

MISSED APPROACH: Climb to 700 then climbing right turn to 2000 direct ORETE and hold.

ATIS	POTOMAC APP CON	EASTON TOWER ★	GND CON	CLNC DEL
124.475	133.75 254.35	118.525 (CTAF) L	119.075	119.075





CATEGORY	A	B	C	D
LPV DA		258-¾	200 (200-¾)	
LNAV/VNAV DA		625-1⅝	567 (600-1⅝)	
LNAV MDA	600-1 542 (600-1)		600-1⅝ 542 (600-1⅝)	
C CIRCLING	600-1 528 (600-1)	640-1 568 (600-1)	640-1⅝ 568 (600-1⅝)	740-2 668 (700-2)

ELEV 72 D TDZE 58

HIRL Rwy 4-22 L

REIL Rwys 22, 15 and 33 L

MIRL Rwy 15-33 L



NE-3, 18 APR 2024 to 16 MAY 2024
NE-3, 18 APR 2024 to 16 MAY 2024