

WAAS
CH **78220**
W12A

APP CRS
117°

Rwy Idg
TDZE
Apt Elev

3449
940
940

RNAV (GPS) RWY 12
M GRAHAM CLARK DOWNTOWN (PLK)

Baro-VNAV NA when using Branson altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP NA with Branson altimeter setting. Obtain local altimeter setting on CTAF; when not received, use Branson altimeter setting and increase all DA 65 feet and all MDA 80 feet; increase LPV all Cats visibility ½ mile and LNAV/VNAV all Cats visibility ¼ mile.

MISSED APPROACH:
Climb to 3200 direct UZAPO and hold.

SPRINGFIELD APP CON
126.35

UNICOM
122.7 (CTAF) 0

4 NM Holding Pattern RAWBE

3200 ← 297°
117° →

GP 3.10°
TCH 40

*LNAV only

3200 UZAPO

GARYY 2600
BRENL 2.9 NM to RW12

*1.7 NM to RW12

RW12

5.1 NM 2 NM 1.2 NM 1.7 NM

CATEGORY	A	B	C	D
LPV DA	1140-¾ 200 (200-¾)			NA
LNAV/VNAV DA	1416-1⅝ 476 (500-1⅝)			NA
LNAV MDA	1540-1 600 (600-1)			NA
CIRCLING	1560-1 620 (700-1)			NA

REIL Rwys 12 and 30 0

MIRL Rwy 12-30 0

BRANSON, MISSOURI

Orig-B 24JUL14

36°38'N-93°14'W

M GRAHAM CLARK DOWNTOWN (PLK)

RNAV (GPS) RWY 12