# RNAV (GPS) RWY 32

MONDELL FLD (ECS)

| WAAS | APP CRS | Rwy Idg | 5310 |
|---|---|---|---|
| CH 61225 | 316° | TDZE | 4176 |
| W32A | | Apt Elev | 4176 |

RNP APCH.

When Newcastle altimeter setting not received, procedure NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -23°C (-9°F) or above 53°C (128°F). Circling NA northeast of Rwy 14-32. For inop ODAL, increase LNAV/VNAV visibility all Cats and LNAV Cats C/D ⅛ mile. Inop table does not apply to LPV all Cats and LNAV Cats A/B.

ODALS

MISSED APPROACH: Climb to 9500 direct PULVE and hold, continue climb-in-hold to 9500.

| AWOS-3PT | DENVER CENTER | UNICOM |
|---|---|---|
| 118.0 | 127.95 338.2 | 122.8 (CTAF) L |

MISSED APCH FIX

7 NM 136° 316° PULVE




ELEV 4176 TDZE 4176




REIL Rwy 14 L

MIRL Rwy 14-32 L




| CATEGORY | A | B | C | D |
|---|---|---|---|---|
| LPV DA | 4385-1 209 (300-1) | | | |
| LNAV/VNAV DA | 4618-1⅜ 442 (500-1⅜) | | | |
| LNAV MDA | 4600-1 424 (500-1) | | 4600-1⅛ 424 (500-1⅛) | |
| C CIRCLING | 4700-1 524 (600-1) | | 4720-1½ 544 (600-1½) | 5000-2¾ 824 (900-2¾) |



NW-1, 18 APR 2024 to 16 MAY 2024
NW-1, 18 APR 2024 to 16 MAY 2024