ILS or LOC RWY 6
DEADHORSE (SCC) (PASC)

LOC/DME I-SCC	APP CRS	Rwy Idg 6500
109.3	058°	TDZE 67
Chan 30		Apt Elev 67

DME required.

For inop ALS, increase S-ILS 6 Cat E visibility to RVR 4000 and S-LOC 6 Cats C/D/E to RVR 4500.
#RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1500 then climbing right turn to 4000 on heading 170° and SCC VOR/DME R-144 to UVALL/SCC 16 DME and hold.

AFIS	ANCHORAGE CENTER	DEADHORSE RADIO
118.4	134.4 370.9	123.6 (CTAF) L



ELEV 67 | D | TDZE 67



HIRL Rwy 6-24 L

Use I-SCC DME when on the localizer course.
VGSI and ILS glidepath not coincident
(VGSI Angle 3.00/TCH 50).

1500	4000	SCC	UVALL
↑	hdg 170°	R-144	△



CATEGORY	A	B	C	D	E
S-ILS 6#	267/24 200 (200-½)				
S-LOC 6	360/24 293 (300-½)				
C CIRCLING	540-1 473 (500-1)		580-1½ 513 (600-1½)	620-2 553 (600-2)	

AK, 21 MAR 2024 to 16 MAY 2024
AK, 21 MAR 2024 to 16 MAY 2024