WAAS	APP CRS	Rwy Idg	5899
CH 86816	065°	TDZE	470
W06A		Apt Elev	486

RNAV (GPS) RWY 6

LANCASTER COUNTY-MC WHIRTER FLD (LKR)

When VGSI inoperative, Circling Rwy 24 NA at night. Baro-VNAV NA when using Rock Hill altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). DME/DME RNP -0.3 NA. When local altimeter setting not received, use Rock Hill altimeter setting and increase LPV DA 69 feet, LNAV/VNAV DA 98 feet and all MDA 80 feet, and increase LPV, LNAV/VNAV all Cats, LNAV and Circling Cats C and D visibilities ¼ mile. VDP NA when using Rock Hill altimeter setting.

MISSED APPROACH: Climb to 2500 direct SAPSE and hold.

AWOS-3	CHARLOTTE APP CON	GCO	UNICOM
120.825	120.05 307.8	121.725	122.725 (CTAF) L



ELEV 486 TDZE 470



CATEGORY	A	B	C	D
LPV DA	670-¾	200 (200-¾)		
LNAV/VNAV DA	993-2	523 (600-2)		
LNAV MDA	940-1	470 (500-1)	940-1¼ 470 (500-1¼)	940-1½ 470 (500-1½)
CIRCLING	1040-1 554 (600-1)	1060-1 574 (600-1)	1120-1¾ 634 (700-1¾)	1160-2¼ 674 (700-2¼)



MIRL Rwy 6-24 L

REIL Rwys 6 and 24 L

SE-2, 18 APR 2024 to 16 MAY 2024
SE-2, 18 APR 2024 to 16 MAY 2024