# RNAV (GPS) RWY 5

## ALBERT J ELLIS (OAJ)

| WAAS | APP CRS | | |
|---|---|---|---|
| CH 49009 | 052° | Rwy Idg | 7100 |
| W05A | | TDZE | 89 |
| | | Apt Elev | 93 |

T A Baro-VNAV NA when using Wilmington altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 43°C (109°F). DME/DME RNP -0.3 NA. VDP NA with Wilmington altimeter setting. When local altimeter setting not received, use Wilmington altimeter setting and increase LPV DA to 383 feet; increase LNAV/VNAV DA to 559 feet and all visibilities ⅜ SM. Increase all MDAs 100 feet and LNAV visibility Cat C/D ⅜ SM, and Circling visibility Cat C/D ¼ SM. For inoperative MALSR, increase LNAV Cat C/D visibility to 1 mile. For inoperative MALSR, when using Wilmington altimeter setting, increase LPV all Cats visibility to ⅞ mile, increase LNAV/VNAV all Cats to 1½ mile, and LNAV Cat C/D to 1⅜ mile.

MALSR

MISSED APPROACH: Climb to 900 then climbing left turn to 2100 direct CUVAL and hold.

| ATIS | WILMINGTON APP CON ★ | ELLIS TOWER ★ | GND CON | CLNC DEL | UNICOM |
|---|---|---|---|---|---|
| 124.475 | 135.75 317.425 | 132.65 (CTAF) L | 125.4 | 121.4 257.6 (when twr closed) | 122.95 |







| CATEGORY | A | B | C | D |
|---|---|---|---|---|
| LPV DA | 289-½ | 200 (200-½) | | |
| LNAV/VNAV DA | 465-¾ | 376 (400-¾) | | |
| LNAV MDA | 460-½ | 371 (400-½) | 460-⅝ | 371 (400-⅝) |
| CIRCLING | 540-1 447 (500-1) | 560-1 467 (500-1) | 720-1¾ 627 (700-1¾) | 720-2 627 (700-2) |







SE-2, 18 APR 2024 to 16 MAY 2024