RNAV (GPS) RWY 17

CHESTER CATAWBA RGNL (DCM)

WAAS CH 93818 W17A	APP CRS 174°	Rwy Idg 5000 / TDZE 657 / Apt Elev 657

RNP APCH-GPS.

Circling to Rwy 5-23 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C. Visibility reduction by helicopters NA. When local altimeter setting not received, use Rock Hill altimeter setting and increase all DA 33 feet and all MDA 40 feet and LNAV Cat D visibility ¼ mile. Baro-VNAV and VDP NA when using Rock Hill altimeter setting.

MISSED APPROACH: Climb to 3000 direct HUSNY and hold.

AWOS-3	CHARLOTTE APP CON	UNICOM
120.975	120.05 307.8	122.7 (CTAF) L





CATEGORY	A	B	C	D
LPV DA	907-1 250 (300-1)			
LNAV/VNAV DA	1134-1¾ 477 (500-1¾)			
LNAV MDA	1060-1 403 (500-1)		1060-1¼ 403 (500-1¼)	
CIRCLING	1160-1 503 (600-1)		1280-1¾ 623 (700-1¾)	1480-2¾ 823 (900-2¾)



MIRL Rwy 17-35 L

SE-2, 18 APR 2024 to 16 MAY 2024
SE-2, 18 APR 2024 to 16 MAY 2024