VOR RWY 18

ST CHARLES COUNTY RGNL/SMARTT FLD (SET)

VORTAC STL	APP CRS	Rwy Idg	3800
117.4	208°	TDZE	437
Chan 121		Apt Elev	437

When local altimeter setting not received, use St Louis Lambert Intl altimeter setting and increase all MDAs 60 feet and Circling visibility Cat C ¼ SM. NUPDE fix minimums: increase Circling visibility Cat C ¼ SM. Straight-in minimums NA with St Louis Lambert Intl altimeter setting.

MISSED APPROACH: Climb to 1000 then climbing left turn to 2700 via heading 360° and STL R-031 to FASHE INT/19.4 DME and hold.

ASOS	ST. LOUIS APP CON	CLNC DEL	UNICOM
118.075	124.2 353.9	121.6	122.7 (CTAF) L





FAF to MAP 5 NM					
Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40



CATEGORY	A	B	C	D
S-18	1160-1 723 (800-1)		1160-2 723 (800-2)	NA
CIRCLING	1160-1 723 (800-1)		1220-2¼ 783 (800-2¼)	NA
NUPDE FIX MINIMUMS				
S-18	800-1 363 (400-1)			NA
CIRCLING	840-1 403 (500-1)	900-1 463 (500-1)	1220-2¼ 783 (800-2¼)	NA

NC-3, 18 APR 2024 to 16 MAY 2024
NC-3, 18 APR 2024 to 16 MAY 2024