RNAV (GPS) RWY 24

COLUMBUS COUNTY MUNI (CPC)

WAAS	APP CRS	Rwy Idg	5500
CH 86638	235°	TDZE	86
W24A		Apt Elev	99

RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Elizabethtown altimeter setting. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Elizabethtown altimeter setting and increase LPV DA to 427 feet, LNAV/VNAV DA to 441 feet and all visibilities ¼ mile. Increase all MDA 60 feet and all Cat C and D visibilities ¼ mile.

MISSED APPROACH: Climb to 2000 direct WADED and hold.

AWOS-3	MYRTLE BEACH APP CON ★	UNICOM
118.375	119.2 350.3	122.8 (CTAF) L



ELEV 99 TDZE 86

2000 WADED

VGSI and RNAV glidepath not coincident (VGSI Angle 3.25/TCH 42).

*LNAV only.





CATEGORY	A	B	C	D
LPV DA	374-1	288 (300-1)		
LNAV/VNAV DA	388-1⅛	302 (300-1⅛)		
LNAV MDA	460-1	374 (400-1)		
C CIRCLING	520-1 421 (500-1)	580-1 481 (500-1)	680-1½ 581 (600-1½)	780-2¼ 681 (700-2¼)

REIL Rwys 6 and 24 L
MIRL Rwy 6-24 L

SE-2, 18 APR 2024 to 16 MAY 2024
SE-2, 18 APR 2024 to 16 MAY 2024