RNAV (GPS) RWY 18

MESQUITE METRO (HQZ)

WAAS CH 58301 W18A	APP CRS 178°	Rwy Idg 6000 / TDZE 447 / Apt Elev 447

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Dallas Love Fld altimeter setting and increase all DA/MDA 60 feet. Increase LPV all Cats visibility to 1 mile, LNAV Cat C visibility to 1⅜ and Circling Cat C visibility to 2¼. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 3000 direct IKUSE then on track 117° to YEAGR and hold.

AWOS-3	REGIONAL APP CON	MESQUITE TOWER★	GND CON	UNICOM
118.175	125.2 343.65	120.3 (CTAF) L	118.85	123.05







CATEGORY	A	B	C	D
LPV DA	697-¾ 250 (300-¾)			NA
LNAV MDA	860-1 413 (500-1)		860-1⅛ 413 (500-1⅛)	NA
C CIRCLING	960-1 513 (600-1)		1160-2 713 (800-2)	NA

MIRL Rwy 18-36 L
REIL Rwys 18 and 36 L
RLLS Rwys 18 and 36 L

SC-2, 18 APR 2024 to 16 MAY 2024
SC-2, 18 APR 2024 to 16 MAY 2024