

LOC/DME I-JNX
111.15
Chan **48** (Y)

APP CRS
032°

Rwy Idg **5500**
TDZE **147**
Apt Elev **164**

ILS Y or LOC Y RWY 3

JOHNSTON RGNL (JNX)

GPS required. VDP NA with Erwin altimeter setting. When local altimeter setting not received, use Erwin altimeter setting: increase DA to 447 feet, increase all MDA 60 feet and S-LOC 3 Cat C/D and Circling Cat A visibility ¼ mile, and JONIR fix minimums S-LOC 3 Cat C/D visibility ⅓ mile and Circling Cat C ¼ mile. For inop MALSR, increase S-LOC 3 Cat C/D visibility to 2½ mile and JONIR fix minimums S-LOC 3 Cat C/D to 1¾ mile. For inop MALSR when using Erwin altimeter setting, increase S-ILS all Cats visibility to 1 mile.

MALSR

AS

MISSED APPROACH: Climb to 3400 direct JNALL and hold, continue climb-in-hold to 3400.

AWOS-3 120.225	RALEIGH APP CON 125.3 353.675	GCO 135.075	UNICOM 122.725 (CTAF) 0
--------------------------	---	-----------------------	--

MISSED APCH FIX

212°

032°

4 NM

JNALL

LOCALIZER 111.15

I-JNX

Chan 48 (Y)

SEYMOUR JOHNSON ECHO MOA

30 NM to WITIX

122°

302°

3000

4000

WITIX (NoPT)

GPS REQUIRED

4 NM Holding Pattern

WITIX I-JNX **12.3**

3000

212°

032°

GS 3.00° TCH 45

7 NM

1.8 NM

0.5

1.8 NM

3400

JNALL

*LOC only.

CATEGORY

A

B

C

D

S-ILS 3	397-½ 250 (300-½)			
S-LOC 3	940-½ 793 (800-½)	940-¾ 793 (800-¾)	940-1¾ 776 (800-2½)	793 (800-1¾)
CIRCLING	940-1 776 (800-1)	940-1¼ 776 (800-1¼)	940-2½ 776 (800-2½)	1100-3 936 (1000-3)
JONIR FIX MINIMUMS				
S-LOC 3	780-½ 633 (700-½)	780-1¾ 633 (700-1¾)	920-2¼ 756 (800-2¼)	1100-3 936 (1000-3)
CIRCLING	780-1 616 (700-1)			

ELEV 164

TDZE 147

032° 4.1 NM from FAF

MIRL Rwy 3-21

REIL Rwy 21

SMITHFIELD, NORTH CAROLINA

JOHNSTON RGNL (JNX)

ILS Y or LOC Y RWY 3

Amdt 1A 18AUG16

35°32'N-78°23'W