

APP CRS
051°

Rwy Idg
2500

TDZE
1209

Apt Elev
1209

RNAV (GPS) RWY 4
SEAMANS FLD (9N3)

▼

▲ NA

DME/DME RNP-0.3 NA.
Obtain local altimeter setting on CTAF; when not received,
use Wilkes-Barre/Scranton Intl altimeter setting.
VDP NA when using Wilkes-Barre/Scranton Intl altimeter setting.

MISSED APPROACH: Climbing left
turn to 4000 direct LOPEZ and hold.

WILKES-BARRE APP CON
120.95 256.7

UNICOM
122.7 (CTAF) 0

The main chart displays the RNAV (GPS) RWY 4 approach. Key features include:

- Initial Approach:** From the south, a 4000 NoPT (12.2) climb to 4000, then a 4000 NoPT (10.4) to 2851, and a 4000 NoPT (1.42) to 2816.
- LOPEZ (IF/IAF):** Located at 2816, with a 4 NM holding pattern at 4000.
- CEMUS (FAF):** Located at 2216, with a 4000 071° (5.2) climb.
- FENUN:** Located at 2145, with a 2.6 NM to RW04.
- RW04:** Runway 4, located at 2139.
- Altitudes:** Various MSL altitudes are marked: 2851, 2816, 2216, 2145, 2139, 2156, 2356, 2729, 2289.
- Obstacles:** Obstacles are marked with their MSL altitudes: 2851, 2816, 2216, 2145, 2139, 2156, 2356, 2729, 2289.
- MSA:** Minimum Safe Altitude (MSA) for RW04 25 NM is 4000.

ELEV 1209 | TDZE 1209

Runway 4-22 is shown with a length of 2200 x 50 feet. The orientation is 051°.

LRL Rwy 4-22 0

4 NM Holding Pattern			
LOPEZ CEMUS			
4000 251° 071° 4000 051° FENUN 2.6 NM to RW04 1.1 NM to RW04 RW04			
3.49° TCH 40 2180			
5.2 NM 4.9 NM 1.5 NM 1.1			
CATEGORY	A	B	C D
LNAV MDA	1640-1	431 (500-1)	NA
CIRCLING	1720-1 511 (600-1)	1780-1 571 (600-1)	NA
WILKES-BARRE/SCRANTON INTL ALTIMETER SETTING MINIMUMS			
LNAV MDA	1720-1	511 (600-1)	NA
CIRCLING	1800-1 591 (600-1)	1860-1 651 (700-1)	NA

FACTORYVILLE, PENNSYLVANIA

Orig-A 14JUL22

41°35'N-75°45'W

SEAMANS FLD (9N3)

RNAV (GPS) RWY 4