WAAS	APP CRS	Rwy Idg 4300
CH 93910	272°	TDZE 22
W27A		Apt Elev 22

RNAV (GPS) RWY 27L

NORTH PALM BEACH COUNTY GENERAL AVIATION (F45)

Circling NA to Rwys 9L and 27R. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Palm Beach Intl altimeter setting. DME/DME RNP-0.3 NA. When local altimeter not received, use Palm Beach Intl altimeter setting and increase LPV DA to 369 feet and all visibilities ⅛ SM; increase LNAV/VNAV DA to 423 feet and all visibilities ⅛ SM; increase all MDA 40 feet and Cat C/D visibility ⅛ SM. Rwy 27L helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 2500 direct YIGBO and hold.

AWOS-3	PALM BEACH APP CON	CLNC DEL	UNICOM
119.975	128.3 317.4	120.825	123.075 (CTAF) L



ELEV 22 TDZE 22





CATEGORY	A	B	C	D
LPV DA	341-⅞	319 (400-⅞)		
LNAV/VNAV DA	395-1	373 (400-1)		
LNAV MDA	380-1	358 (400-1)		
C CIRCLING	460-1 (438 (500-1))	480-1 (458 (500-1))	700-2 (678 (700-2))	720-2¼ (698 (700-2¼))

MIRL Rwys 9R-27L and 14-32 L
REIL Rwys 9R, 14, 27L and 32 L

SE-3, 18 APR 2024 to 16 MAY 2024