# RNAV (GPS) Z RWY 18

PICAYUNE MUNI (MJD)

| WAAS | APP CRS | Rwy Idg | 5000 |
|---|---|---|---|
| CH 99310 | 179° | TDZE | 55 |
| W18B | | Apt Elev | 55 |

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Stennis Intl altimeter setting. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. Procedure NA when R-4403 B, C, or E is active. When local altimeter setting not received, used Stennis Intl altimeter setting: increase LPV DA to 377 and visibility all Cats ⅛ mile; increase LNAV/VNAV DA to 621 and visibility all Cats ⅛ mile; increase all MDA 40 feet and Circling Cat C visibility ¼ mile.

MISSED APPROACH: Climb to 1200, then climbing right turn to 1800 direct CIQYI and hold.

| AWOS-3PT | GULFPORT APP CON★ | UNICOM |
|---|---|---|
| 119.075 | 124.6 354.1 | 122.8 (CTAF) L |










| CATEGORY | A | B | C | D |
|---|---|---|---|---|
| LPV DA | 343-1 288 (300-1) | | | |
| LNAV/VNAV DA | 587-1⅞ 532 (600-1⅞) | | | |
| LNAV MDA | 520-1 465 (500-1) | | 520-1⅜ 465 (500-1⅜) | |
| C CIRCLING | 520-1 465 (500-1) | 580-1 525 (600-1) | 700-1¾ 645 (700-1¾) | 960-3 905 (1000-3) |



SC-4, 18 APR 2024 to 16 MAY 2024
SC-4, 18 APR 2024 to 16 MAY 2024