

LOC/DME I-JNX
111.15
Chan 48 (Y)

APP CRS
032°

Rwy Idg **5500**
TDZE **147**
Apt Elev **164**

ILS Z or LOC Z RWY 3

JOHNSTON RGNL (JNX)

ADF required. ADF or RADAR required for procedure entry.
DME or RADAR required for LOC only.

▼


NA

VDP NA with Erwin altimeter setting. When local altimeter setting not received, use Erwin altimeter setting: increase DA to 447 feet and all MDAs 60 feet; increase S-LOC 3 Cats C/D and Circling Cat A visibility ¼ SM; JONIR DME fix minimums increase S-LOC 3 Cats C/D visibility ½ SM and Circling Cat C visibility ¼ SM. For inop ALS, increase S-LOC 3 Cats C/D visibility to 2 ½ SM; increase JONIR DME fix minimums Cats C/D visibility to 1 ¾ SM. For inop ALS when using Erwin altimeter setting, increase S-ILS all Cats visibility to 1 SM.

MALSR

MISSED APPROACH: Climb to 1000 then climbing right turn to 1800 direct JN NDB and hold.

AWOS-3 120.225	RALEIGH APP CON 125.3 353.675	GCO 135.075	UNICOM 122.725 (CTAF) 0
--------------------------	---	-----------------------	--



Remain within 10 NM

1800

212°

032°

GS 3.00° TCH 45

JHDI I-JNX RADAR 1500

JONIR I-JNX 3.5

JN NDB 1000

1800

JN

*LOC only.

1500

032°

*940

1.8 NM

0.5

1.8 NM

CATEGORY	A	B	C	D
S-ILS 3	397-½ 250 (300-½)			
S-LOC 3	940-½ 793 (800-½)	940-¾ 793 (800-¾)	940-1¼ 776 (800-1¼)	793 (800-1¼)
CIRCLING	940-1 776 (800-1)	940-1¼ 776 (800-1¼)	940-2½ 776 (800-2½)	1100-3 936 (1000-3)
JONIR DME FIX MINIMUMS				
S-LOC 3	780-½ 633 (700-½)	780-1¾ 633 (700-1¾)	780-1¾ 633 (700-1¾)	
CIRCLING	780-1 616 (700-1)	920-2¼ 756 (800-2¼)	1100-3 936 (1000-3)	

ELEV 164

TDZE 147

FAF to MAP 4.1 NM

Knots 60 90 120 150 180

Min:Sec 4:06 2:44 2:03 1:38 1:22