

LIHUE (LIH)(PHLI) 2 E UTC-10 N21°58.56' W159°20.34'
 152 B TPA—See Remarks LRA Class I, ARFF Index C NOTAM FILE LIH
RWY 03-21: H6500X150 (ASPH-GRVD) S-75, D-200, 2D-350, 2D/2D2-730
 PCN 75 F/A/W/T MIRL
RWY 03: REIL. PAPI(P4L)—GA 3.0° TCH 46'. Rgt tfc. 1.1% up SW.
RWY 21: REIL. PAPI(P4L)—GA 3.0° TCH 45'. Thld dspclcd 205'. Tree.
RWY 17-35: H6500X150 (ASPH-GRVD) S-75, D-175, 2D-250, 2D/2D2-630 PCN 75 F/A/W/T HIRL
RWY 17: REIL. PAPI(P4L)—GA 3.0° TCH 54'.
RWY 35: MALSR. PAPI(P4L)—GA 3.0° TCH 55'. Rgt tfc.

HAWAIIAN ISLANDS
 P-2F
 IAP

RUNWAY DECLARED DISTANCE INFORMATION

RWY 03: TORA-6500 TODA-6500 ASDA-6500 LDA-6500
RWY 17: TORA-6500 TODA-6500 ASDA-6500 LDA-6500
RWY 21: TORA-6500 TODA-6500 ASDA-6500 LDA-6295
RWY 35: TORA-6500 TODA-6500 ASDA-6500 LDA-6500

SERVICE: S2 **FUEL** 100, JET A **LGT** When ATCT clsd ACTVT MALSR Rwy 35; REIL Rwys 03, 17 and 21; PAPI Rwy 03, 17, 21, and 35; MIRL Rwy 03-21; HIRL Rwy 17-35; twy lgts—CTAF. PAPI Rwy 03 unusable byd 1.5 NM and 7° left of centerline and offset 9.5° E of centerline due to rapidly rising terrain. PAPI Rwy 17 unusable byd 5° rgt of centerline.
AIRPORT REMARKS: Attended 1600-0800Z. Extensive large and small bird activity in/ovf rwy including the nene goose.

Stadium flood lights 125' AGL/282' MSL 2400' SW from Rwy 03 threshold. PPR for parking all transient acft, call arpt ops control (808) 651-6255; fax (808) 241-3939 btn 1700Z and 0230Z; other times, call (808) 274-3814.
 Military/civilian acft carrying munitions/HAZMAT must coordinate itinerary no later than 24 hours prior to arrival. Acft needing eng runups for otr than nml start-up and taxi out are rprd to coord these runups with ops at 808-651-6255.
 Nml runup area is on Twy Alpha north of Twy B and Alpha int. Acft orientation is dependent on wind and twr apvl. Power setting will not cause damage to lgts and signs, if run may cause damage an alternate location will be selected. Rwy 17-35 dist rmng signs left side of Rwy 35. 405 ft of Rwy 17-35 500 ft south of Twy D and Rwy 17-35 int not vsb fm ATCT. Due to non-visibility twr unable to provide air traffic control svc between acft and/or vehicles on Twy B from 220' to 500' S of Twy D. Tfc departing and entering movement areas ctc twr. Intersection departures from Twy D on Rwy 17-35 not authorized. ARFF available 24 hrs. 100 octane fuel available 1900-0300Z. For JET A fuel call 1 (800) 776-2138 or 1 (800) 821-3122. Military acft make fuel arrangements before arrival. PPR for transportation of Div 1.1, 1.2, 1.3, 1.4 explosives and hazmat in and out of arpt. Call Arpt Ops at 808-651-6255. Rwy 17-35 wgt lmt DC 10-10 340,000 lbs; DC 10-30 430,000 lbs. TPA—single engine 1000(847), Multi engine 1500(1347).

AIRPORT MANAGER: (808) 274-3800
WEATHER DATA SOURCES: ASOS (808) 246-3707
COMMUNICATIONS: CTAF 118.9 ATIS 127.2
 RCO 122.4 122.1R 113.5T (HONOLULU RADIO)
TOWER 118.9 (128.4 Helicopters) (1600-0800Z) (when twr clsd ctc HCF)
 (R) HCF CENTER APP/DEP CON - CLNC DEL 126.5 269.4 (If unavailable ctc 134.0)
 GND CON 121.9

CLEARANCE DELIVERY PHONE: For CD when ATCT is clsd ctc Honolulu Control Facility at 808-840-6262.

AIRSPACE: CLASS D svc 1600-0800Z other times CLASS E.

RADIO AIDS TO NAVIGATION: NOTAM FILE LIH.

(H) VORTAC 113.5 LIH Chan 82 N21°57.92' W159°20.29' at fld. 101/11E.

TACAN AZIMUTH and DME unusable:

180°-240° byd 16 NM
 241°-330° byd 18 NM
 331°-355° byd 30 NM blo 7,500'

VOR unusable:

180°-240° byd 33 NM blo 11,500'
 241°-330° byd 18 NM
 331°-355° byd 30 NM blo 7,500'

ILS/DME 110.9 I-LIH Chan 46 Rwy 35. Class IE. LOC unusable byd 20° left of course. ILS/DME unmonitored when ATCT closed. DME unusable byd 20° left of course.

ASR

COMM/NAV/WEATHER REMARKS: When twr closed, A/C on ground ctc Honolulu Center (HCF) on 126.5/ HCF Apch 134.0.

HELIPAD H1: H40X40 (CONC)

HELIPAD H2: H40X40 (CONC)

HELIPAD H3: H40X40 (CONC)

HELIPORT REMARKS: Helicopter pads 1 through 20 located west of control twr.

NORTH KAUAI N22°12.55' W159°26.63'
 RCO 122.3 (HONOLULU RADIO)

HAWAIIAN-MARIANA
 P-2F