VOR RWY 13

TEXARKANA RGNL-WEBB FLD (TXK)

VORTAC TXK	APP CRS	Rwy Idg	4559
116.3	122°	TDZE	387
Chan 110		Apt Elev	390

When local altimeter setting not received, use J Lynn Helms Sevier County altimeter setting and increase all MDA 100 feet, increase S-13 and circling Cat C and D visibility ¼ mile. Visibility reduction by helicopters NA. VDP NA when using J Lynn Helms Sevier County altimeter setting.

MISSED APPROACH: Climb to 1500 then climbing right turn to 2000 direct TXK VORTAC and hold.

ATIS	FORT WORTH CENTER	TEXARKANA TOWER ★	GND CON
120.2	123.925 269.475	123.875 (CTAF) L 235.625	119.225







CATEGORY	A	B	C	D
S-13	760-1 373 (400-1)			760-1¼ 373 (400-1¼)
CIRCLING	820-1 430 (500-1)	860-1 470 (500-1)	900-1½ 510 (600-1½)	1000-2 610 (700-2)

MIRL Rwy 13-31 L
HIRL Rwy 4-22 L

FAF to MAP 5.2 NM

Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

SC-1, 09 SEP 2021 to 07 OCT 2021
SC-1, 09 SEP 2021 to 07 OCT 2021