

RADAR INSTRUMENT APPROACH MINIMUMS

DAVISON AAF (KDA), Ft. Belvoir, VA Amdt 11A 16JUL20 (20198) (USA)

ELEV 74

RADAR¹ - (E) 118.85 119.95 248.5x 265.6 **VA** NA

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR	32	3.0°/34/689	ABCD	346/50	278	(300-1)
	14	3.0°/59/1114	ABCD	642-2	582	(600-2)

When control tower clsd procedure NA.

¹Opr 1100-0230Z++ Mon-Fri excld hol.

09 SEP 2021 to 07 OCT 2021

09 SEP 2021 to 07 OCT 2021


RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

NORFOLK NS (CHAMBERS FIELD) (KNGU), Norfolk, VA

Amdt 7 08OCT20 (20282) (USN)

ELEV 15

RADAR - (E) 119.2x 120.2x 279.525 322.525 335.8 353.55 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR ¹	10 ^{2 3}	3.0°/54/1020	ABCDE	114-¼	100	(100-¼)
	28 ⁴	3.0°/37/719	ABCDE	313-¾	299	(300-¾)
PAR W/O GS ¹	28 ⁵		ABCDE	380-¾	366	(400-¾)
	10 ¹⁰		AB	500-⅝	486	(500-⅝)
			CDE	500-1	486	(500-1)
ASR	28 ⁶		ABCDE	460-1	446	(500-1)
	10 ⁹		AB	720-¾	706	(800-¾)
			CDE	720-1⅙	706	(800-1⅙)
C CIR PAR W/O GS ^{7 8}	10		A	500-1	485	(500-1)
			B	560-1	545	(600-1)
			C	560-1½	545	(600-1½)
			D	580-2	565	(600-2)
			E	700-2½	685	(700-2½)
	28		A	540-1⅙	525	(600-1⅙)
			B	740-1⅙	725	(800-1⅙)
			C	780-2¼	765	(800-2¼)
			D	820-2½	805	(900-2½)
			E	820-2¾	805	(900-2¾)
C CIR ASR ^{7 8}	28		A	500-1¼	485	(500-1¼)
			B	560-1¼	545	(600-1¼)
			C	560-1½	545	(600-1½)
			D	580-2	565	(600-2)
			E	700-2½	685	(700-2½)
	10		AB	720-1¼	705	(800-1¼)
			C	720-2	705	(800-2)
			D	720-2¼	705	(800-2¼)
			E	720-2½	705	(800-2½)

09 SEP 2021 to 07 OCT 2021

09 SEP 2021 to 07 OCT 2021

¹No-NOTAM MP Sun 1230-1630Z++.

²When ALS inop, increase vis CAT ABCDE to ½ mile.

³PAPI RRP/TCH 669/35 not coincident with PAR RPI/TCH 1020/54.

⁴When ALS inop, increase vis CAT ABCDE to ⅔ mile.

⁵When ALS inop, increase vis CAT ABCDE to 1⅓ miles.

⁶When ALS inop, increase vis CAT AB to 1¼ miles, CAT CDE to 1⅓ miles.

⁷Cir not auth south of Rwy 10-28.

⁸Norfolk NS Heliport lctd 1 NM NW, use caution in cir aprch.

⁹When ALS inop, increase vis CAT AB to 1¼ miles, CAT CDE to 2 miles.

¹⁰When ALS inop, increase vis CAT AB to 1 mile, CAT CDE to 1⅓ miles.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

21140

N3

RADAR INSTRUMENT APPROACH MINIMUMS

OCEANA NAS (APOLLO SOUCEK FIELD) (KNTU), Virginia Beach, VA

Amdt 6 20MAY21 (21140) (USN)

RADAR - (E) 124.825 310.8 328.4 346.4 348.75 352.1 363.1 **▼**

ELEV 22

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/</u>	<u>CEIL-VIS</u>
PAR	5R ¹	3.0°/40/758	ABCDE	119-¼	100	(100-¼)
	23L ¹	3.0°/40/769	ABCDE	121-¼	100	(100-¼)
	32L ¹	3.0°/40/762	ABCDE	122-¼	100	(100-¼)
	5L	3.0°/40/766	ABCDE	120-½	100	(100-½)
	23R	3.0°/40/771	ABCDE	121-½	100	(100-½)
	32R	3.0°/40/770	ABCDE	121-½	100	(100-½)
SIDESTEP ³	5L		ABCDE	440-1⅞	420	(500-1⅞)
	23L		ABCDE	460-1¼	439	(500-1¼)
	23R		ABCDE	460-1¼	439	(500-1¼)
	32R		ABCDE	460-1¼	439	(500-1¼)
ASR ⁴	5R ²		AB	440-¾	421	(500-¾)
			CDE	440-¾	421	(500-¾)
	23L ²		AB	460-¾	439	(500-¾)
			CDE	460-¾	439	(500-¾)
	32L ²		AB	460-¾	438	(500-¾)
			CDE	460-¾	438	(500-¾)
	5L		AB	440-1	420	(500-1)
			CDE	440-1⅞	420	(500-1⅞)
	14L		AB	460-1	440	(500-1)
			CDE	460-1¼	440	(500-1¼)
	14R		AB	460-1	439	(500-1)
			CDE	460-1¼	439	(500-1¼)
	23R		AB	460-1	439	(500-1)
			CDE	460-1¼	439	(500-1¼)
32R		AB	460-1	439	(500-1)	
		CDE	460-1¼	439	(500-1¼)	
C CIR	ALL RWY		AB	500-1⅞	478	(500-1⅞)
			C	640-1¾	618	(700-1¾)
			D	640-2	618	(700-2)
			E	900-3	878	(900-3)

¹When ALS inop, increase CAT ABCDE vis to ½ mile.

²When ALS inop, increase CAT AB vis to 1 mile, CAT CDE to 1¼ miles.

³Sidestep ASR only.

⁴Step Down Fix at 3 NM from thld, 1020' min.

09 SEP 2021 to 07 OCT 2021

09 SEP 2021 to 07 OCT 2021

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

21140

N3

NE-3

RADAR INSTRUMENT APPROACH MINIMUMS

PATUXENT RIVER NAS (TRAPNELL FIELD) (KNHK), Patuxent River, MD

Amdt 1 10SEP20 (20254) (USN)

ELEV 39

RADAR - (E) 120.05 121.0 135.025 250.3 257.75 281.8 318.8 348.0 362.6 **▼**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
PAR ¹	6 ²	3.0°/46/999	ABCDE	139 - ³ / ₄	100	(100- ³ / ₄)
	24	3.0°/45/857	ABCDE	120 - ¹ / ₂	100	(100- ¹ / ₂)
	14	3.0°/42/814	ABCDE	127 - ¹ / ₂	100	(100- ¹ / ₂)
	32	3.0°/48/906	ABCDE	266 - ³ / ₄	250	(300- ³ / ₄)
PAR W/O GS	14		ABCDE	360 -1	333	(400-1)
	24		ABCDE	360 -1	340	(400-1)
	32		ABCDE	340 -1	324	(400-1)
	6 ⁴		AB	460 - ¹ / ₂	421	(500- ¹ / ₂)
			CDE	460 - ³ / ₄	421	(500- ³ / ₄)
ASR	14		ABCDE	400 -1	373	(400-1)
	32		AB	400 -1	384	(400-1)
			CDE	400 -1 ¹ / ₆	384	(400-1 ¹ / ₆)
	6 ³		AB	520 - ¹ / ₂	481	(500- ¹ / ₂)
			CDE	520 -1	481	(500-1)
	24		AB	440 -1	420	(500-1)
		CDE	440 -1 ¹ / ₆	420	(500-1 ¹ / ₆)	
CIR	6-24, 14-32		A	560 -1	521	(600-1)
			B	600 -1	561	(600-1)
			C	620 -1 ¹ / ₂	581	(600-1 ¹ / ₂)
			D	660 -2	621	(700-2)
			E	800 -2 ³ / ₄	761	(800-2 ³ / ₄)

09 SEP 2021 to 07 OCT 2021

09 SEP 2021 to 07 OCT 2021

¹PAR No-NOTAM preventive maint period Wed 1300-1700Z++.

²When ALS inop, increase CAT ABCDE vis to ¹/₂ mile.

³When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1¹/₆ miles.

⁴When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1¹/₆ miles.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

QUANTICO MCAF (TURNER FIELD) (KNYG), Quantico, VA Amdt 6

05NOV20 (20310) (USN)

ELEV 11

RADAR¹ - 120.925 351.95 353.65 363.15 **▼**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR ⁴	2	3.0°/35/666	ABCD	260 -¾	250	(300-¾)
ASR ²	2		AB CD	560 -1½ 560 -1%	549 550	(600-1½) (600-1%)
CIR ASR ³	2		A B C D	560 -1½ 640 -1½ 720 -2 800 -2½	549 629 709 789	(600-1½) (700-1½) (800-2) (800-2½)

¹GCA avbl daily during published field opr hours. Ctc twr for freq asgn.

²VGSI and final descent angle not coincident.

³Circling NA W of Rwy 2-20.

⁴WCH (Group 3: 15 ft, Group 4: 10 ft) is less than the minimum height (20 ft).

09 SEP 2021 to 07 OCT 2021

09 SEP 2021 to 07 OCT 2021

RADAR INSTRUMENT APPROACH MINIMUMS