

WAAS CH <b>63199</b> <b>W17A</b>	APP CRS <b>174°</b>	Rwy Idg TDZE Apt Elev	<b>7351</b> <b>843</b> <b>845</b>
--	------------------------	-----------------------------	---

# RNAV (GPS) RWY 17R

GRAND FORKS INTL (GFK)




RNP APCH.

**⚠** Baro-VNAV NA when using Crookston altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. VDP NA with Crookston altimeter setting.

**⚠** When local altimeter setting not received, use Crookston altimeter setting and increase all DA 62 feet and all MDA 80 feet and increase LPV and LNAV/VNAV all Cats visibility 1/8 SM, LNAV Cats C/D visibility 1/8 SM, and Circling Cat C visibility 1/4 SM.

MISSED APPROACH:  
Climb to 2600 direct ERIXE and hold.

ATIS <b>119.4</b>	GRAND FORKS APP CON* <b>118.1 318.1</b>	GRAND FORKS TOWER* <b>118.4(CTAF) 350.35</b>	GND CON <b>124.575</b>	CLNC DEL <b>135.725</b>	UNICOM <b>122.95</b>
----------------------	--	---	---------------------------	----------------------------	-------------------------



CATEGORY	A	B	C	D
LPV DA		1043-3/4	200 (200-3/4)	
LNAV/VNAV DA		1093-3/4	250 (300-3/4)	
LNAV MDA		1180-1	337 (400-1)	
CIRCLING	1260-1 415 (500-1)	1300-1 455 (500-1)	1400-1 1/2 555 (600-1 1/2)	1400-2 555 (600-2)

NC-1, 08 SEP 2022 to 06 OCT 2022

NC-1, 08 SEP 2022 to 06 OCT 2022