

WAAS CH 56214 W36A	APP CRS 357°	Rwy Idg 12901 TDZE 1175 Apt Elev 1219
--	------------------------	--

RNAV (GPS) RWY 36

LINCOLN (LNK)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Beatrice altimeter setting and increase all DA 91 feet, all MDA 100 feet and LNAV/VNAV all Cats, LNAV Cat C and D, and Circling Cats C and D visibility ¼ mile and LPV all Cats visibility ½ mile. For inop MALSR increase LPV all Cats visibility to 1 mile. For inop MALSR when using Beatrice altimeter setting increase LPV all Cats visibility to 1½ mile. Baro-VNAV and VDP NA when using Beatrice altimeter setting.

MALSR

MISSED APPROACH:

Climb to 3800 direct AYARE and hold.

ATIS 118.05 290.9	OMAHA APP CON 124.0 270.3	LINCOLN TOWER ★ 118.5 (CTAF) 253.5	GND CON 121.9 275.8	CLNC DEL 120.7 225.4	UNICOM 122.95
-----------------------------	-------------------------------------	--	-------------------------------	--------------------------------	-------------------------

30 NM to HEGLU
14 NM to HEGLU
HEGLU
087°

1448A
1355A
1367A
2800
357° (6)
177°
4 NM

1341
1651
1734
1594A

(FAF) JUDAD

(IAF) HEGLU 3700 NoPT 087° (5)
(IF/IAF) GONBE
(IAF) JESUR 3700 NoPT 267° (5)

30 NM to JESUR
JESUR
177°
267°
3700

2037A

2438A

087°
267°
3700
30 NM to GONBE (NoPT)

ELEV 1219 D TDZE 1175

MIRL Rwy 14-32 and 17-35
REIL Rwy 14 and 17
HIRL Rwy 18-36

81
1241
0.43 DOWN
1200 X 200
TWR 1280
36
357° to RW36

4 NM Holding Pattern GONBE

3700 177° 357°

JUDAD 2800

GP 3.00° TCH 56

2800

6 NM 3.7 NM 1.2 NM

3800 AYARE

*1.2 NM to RW36

*LNAV only

RW36

CATEGORY	A	B	C	D
LPV DA	1493/24 318 (300-½)			
LNAV/VNAV DA	1669/60 494 (500-1¼)			
LNAV MDA	1620/24 445 (500-½)	1620/40 445 (500-¾)		1620/50 445 (500-1)
CIRCLING	1720-1 501 (600-1)	1760-1 541 (600-1)	1820-1¼ 601 (700-1¾)	1960-2½ 741 (800-2½)

LINCOLN, NEBRASKA

Amtd 1D 12AUG21

40°51'N-96°46'W

LINCOLN (LNK)

RNAV (GPS) RWY 36