

APP CRS
038°

Rwy Idg
TDZE
3607

Apt Elev
3607

RNAV (RNP) Z RWY 4

RICK HUSBAND AMARILLO INTL (AMA)

T For uncompensated Baro-VNAV systems, procedure NA below -14°C (7°F) or above 53°C (128°F). RF required. GPS required. For inop ALS, increase RNP 0.30 all Cats visibility to 1½ SM.

ASR

MALSR

MISSED APPROACH: (Do not exceed 185K until MAWGO) Climb to 5400 on track 038° to KILTE, right turn to MAWGO, then track 157° to CAUDE and hold.

ATIS 118.85 350.3	AMARILLO APP CON★ 119.5 307.0	AMARILLO TOWER★ 118.3(CTAF) 257.9	GND CON 121.9 348.6	CLNC DEL 121.65 239.275	UNICOM 122.95
-----------------------------	---	---	-------------------------------	-----------------------------------	-------------------------

RNAV 1 - GPS or RADAR REQUIRED

MSA RW04 25 NM
6100

Waypoints and Altitudes:
TEXAZ 6100 (IF)
DONSS 210K until CUBIB
PUKTE 4600 (1.9)
HUBUG 210K until CUBIB
JOPNI 5100 (2.2)
MOZFO 5700 (IF)
VASSY 210K until CUBIB
KILTE 3726
MAWGO
VERRO 5200 (IF)
CAUDE 298 (18.5)
WESTX 5200 (IF)
PLNZE 210K until CUBIB
RW04 3754
CUBIB 4600 (3)
P-47

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 61).

5400 KILTE

MAWGO

CAUDE

See planview for multiple IF locations.

GP 3.00°

TCH 44

4600

038°

3 NM

RW04

CATEGORY	A	B	C	D
RNP 0.12 DA		3969/40	362 (400-¾)	
RNP 0.30 DA		4019/50	412 (500-1)	

AUTHORIZATION REQUIRED

ELEV 3607

TDZE 3607

REIL Rwy 13
HIRL Rwy 4-22 and 13-31

AMARILLO, TEXAS
Amdt 1 12OCT17

35°13'N-101°42'W

RICK HUSBAND AMARILLO INTL (AMA)
RNAV (RNP) Z RWY 4