

WAAS
CH **82718**
W04A

APP CRS
038°

Rwy Idg **13502**
TDZE **3607**
Apt Elev **3607**

RNAV (GPS) Y RWY 4

RICK HUSBAND AMARILLO INTL (AMA)

RNP APCH.

▼

ASR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 41°C. For inop ALS, increase LPV Cat E visibility to RVR 4000, and LNAV/VNAV and LNAV Cat E to 1¼ SM.
** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

AS

AS

MISSED APPROACH: Climb to 5400 direct CIPLI and on track 053° to ZUKTA and hold.

ATIS 118.85 350.3	AMARILLO APP CON* 119.5 307.0	AMARILLO TOWER* 118.3 (CTAF) 257.9	GND CON 121.9 348.6	CLNC DEL 121.65 239.275	UNICOM 122.95
-----------------------------	---	--	-------------------------------	-----------------------------------	-------------------------

Procedure NA for arrivals at SIDER on V402 southwest bound.

Procedure NA for arrivals at YOCAN on V81 southbound.

Procedure NA for arrivals at CAUDE on V114 southeast bound.

Procedure NA for arrivals at ZUKTA on track 053° to ZUKTA and hold.

MSA RW04 25 NM

6100

5300 085° (6.4) SIDER

5300 128° (9.1) JAXIV

5200 038° (6) MOZFO

5200 308° (5) JOPNI

5300 308° (5) ROTGY

5400 338° (16.5) YOCAN

4148 3882 3726 3773 3754 3745

WEKOB 1.9 NM to RW04

(FAF) JOPNI

Tradewind

CAUDE 5300 245° (17.3)

ZUKTA 233° 053° 5 NM

P-47

MISSED APCH FIX

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 61).
MOZFO

5300

5200

GP 3.00°
TCH 44

038°

6 NM

2.9 NM

0.8 NM

1.1 NM

RW04

5400

CIPLI

ZUKTA

tr 053°

*LNAV only.

WEKOB 1.9 NM to RW04

*1.1 NM to RW04

RW04

*4240

CATEGORY	A	B	C	D	E
LPV DA **	3807/24		200 (200-½)		
LNAV/VNAV DA	4028/50		421 (500-1)		
LNAV MDA	4040/24	433 (500-½)	4040/40 433 (500-¾)	4040/50	433 (500-1)
CIRCLING	4080-1	473 (500-1)	4240-1¼ 633 (700-1¾)	4280-2¼ 673 (700-2¼)	4460-3 853 (900-3)

TWR 3724

13502 X 200

13502 X 150

038°

REIL Rwy 13

HIRL Rws 4-22 and 13-31

AMARILLO, TEXAS
Amdt 1B 10SEP20

35°13'N-101°42'W

RICK HUSBAND AMARILLO INTL (AMA)
RNAV (GPS) Y RWY 4