

WAAS CH 58336 W28B	APP CRS 276°	Rwy Idg TDZE 65 Apt Elev 65	8000
--	------------------------	---	-------------

RNAV (GPS) RWY 28L

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)

RNP APCH-GPS.

▼

▲

Inop table does not apply to LPV. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 7°C or above 54°C. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.

MALSF

MISSED APPROACH: Climb to 1000 then climbing left turn to 3000 direct GEGEY and hold.

D-ATIS 135.0	MIAMI APP CON 133.775 285.6	FORT LAUDERDALE TOWER 119.3 257.8	GND CON 121.4	CLNC DEL 128.4	CPDLC
------------------------	---------------------------------------	---	-------------------------	--------------------------	-------

MISSED APCH FIX

GEGEY

260°

080°

4 NM

Procedure NA for arrival on FLL VOR/DME airway radials 013 CW 121.

499±

335±

FORT LAUDERDALE FLL

214

310

2500 to WIKIR 099° (12.7)

250±

2000

276° (5)

6000

2500

HOLD

096°

4 NM

2500 NoPT 277° (5.5)

(IAF) ZADIL 5000

2500 NoPT 258° (10.1)

(IAF) CRNVL 5000

1049

1049

510

1049

MSA RW28L 2.5 NM

2100

ELEV 65

D

TDZE 65

1000

3000

GEGEY

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).

WIKIR

4 NM Holding Pattern

YOBUS

2000

1.2 NM to RW28L

276°

096°

6000

2500

GP 3.00° TCH 53

1.2 NM

4.7 NM

5 NM

CATEGORY

A

B

C

D

LPV DA

265/40

200 (200-¾)

LNAV/VNAV DA

459/45

394 (400-⅞)

LNAV MDA

500/40

435 (500-¾)

500/50

435 (500-1)

CIRCLING

680-1

615 (700-1)

800-2 735 (800-2)

800-2¼ 735 (800-2¼)

FORT LAUDERDALE, FLORIDA
Amdt 2 12AUG21

26°04'N-80°09'W

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)

RNAV (GPS) RWY 28L