

RNP APCH

⚠

⚠


W

Circling NA for Cat D southwest of Rwy 13-31. When local altimeter setting not received, use Laughlin AFB altimeter setting and increase all DA 30 feet and all MDA 40 feet, increase LPV visibility all Cats, LNAV Cats C and D and Circling Cats C and D visibility ¼ SM. Baro-VNAV NA when using Laughlin AFB altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17° C (2°F) or above 47°C (116°F).


MALS

MISSED APPROACH: Climb to 4000 direct AREXE and on 069° track to DLF VORTAC and hold, continue climb-in-hold to 4000.

ASOS 118.525	DEL RIO APP CON * 119.6 259.1	CLNC DEL 120.5	UNICOM 122.8 (CTAF)
------------------------	---	--------------------------	-------------------------------



ELEV 1002	D	TDZE 1002
-----------	----------	-----------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 47).			
4 NM	AREXE	tr 069°	DLF
Holding Pattern	JERUL	RORKY	HIBUD 1.9 NM to RW13
4000	312°	2700	1640
GP 3.00°	TCH 48	8.6 NM	3.2 NM 1.9
CATEGORY	A	B	C
LPV DA	1252-3/4	250 (300-3/4)	
LNAV/VNAV DA	1401-1	399 (400-1)	
LNAV MDA	1500-1/2 498 (500-1/2)	1500-3/4 498 (500-3/4)	1500-1 498 (500-1)
CIRCLING	1500-1 498 (500-1)	1560-1 558 (600-1)	1740-2 738 (800-2)