




ILS or LOC RWY 23
JIMMY CARTER RGNL (ACJ)

V **NA** Rwy 23 helicopter visibility reduction below $\frac{3}{4}$ SM NA. When local altimeter setting not received, use Columbus altimeter setting and increase S-ILS 23 DA to 889 and all MDA 120 feet, increase S-ILS 23 all Cats visibility and S-LOC 23 Cat C/D visibility $\frac{1}{4}$ SM, increase Circling Cat C visibility $\frac{1}{2}$ SM, and Circling Cat D visibility $\frac{1}{4}$ SM. For inop ALS when using Columbus altimeter setting increase S-LOC 23 Cat C/D visibility to $1\frac{1}{4}$ SM. Circling Rwy 10, 28 NA at night. For inop ALS, increase S-ILS 23 all Cats visibility to $\frac{3}{4}$ SM.



MISSED APPROACH:
Climb to 1100 then
climbing left turn to
2500 direct LKG NDB
and hold.

AWOS-3 128.375	ATLANTA APP CON ★ 124.2 323.1	CLNC DEL 119.95	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------	--



SE-4, 30 NOV 2023 to 28 DEC 2023

SE-4, 30 NOV 2023 to 28 DEC 2023