

WAAS
CH **99719**
W16A

APP CRS
164°

Rwy Idg
TDZE **99**
Apt Elev
100

RNAV (GPS) RWY 16

YOLO COUNTY (DWA)

RNP APCH.

When local altimeter setting not received, use Travis AFB altimeter setting and increase all DA 50 feet and all MDA 60 feet, and increase LNAV/VNAV all Cats and LNAV Cat C and D visibility ¼ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 43°C (109°F). Baro-VNAV NA when using Travis AFB altimeter setting.

MISSED APPROACH: Climb to 3600 direct PROAP and hold, continue climb-in-hold to 3600.

AWOS-3P
125.775

TRAVIS APP CON
126.6 281.45

UNICOM
123.0 (CTAF)

ELEV 100

TDZE 99

164° to RW16

91

100 x 0009

34

3600	PROAP	GAAAS 1.7 NM to RW16	YOLOH 2000	GHEER	4 NM Holding Pattern
*LNAV only					
		680*	2000	3000	GP 3.00° TCH 40
		1.7 NM	4.2 NM	6.2 NM	
CATEGORY	A	B	C	D	
LPV DA	360-1 261 (300-1)				
LNAV/VNAV DA	402-1 303 (400-1)				
LNAV MDA	480-1 381 (400-1)		480-1½ 381 (400-1½)		

MIRL Rwy 16-34

DAVIS/WOODLAND/WINTERS, CALIFORNIA

YOLO COUNTY (DWA)

Amdt 2C 15AUG19

38°35'N-121°51'W

RNAV (GPS) RWY 16