


WAAS CH 97339 W22A	APP CRS 225°	Rwy Idg 5002 TDZE 107 Apt Elev 112
--	------------------------	---

RNAV (GPS) RWY 22
DEMOPOLIS RGNL (D Y A)


⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F).
⚠ DME/DME RNP-0.3 NA. When local altimeter setting not received, use Marion altimeter setting and increase LPV and LNAV/VNAV DA 82 feet and all MDA 100 feet; increase LPV all Cats visibility ¼ mile, increase LNAV/VNAV all Cats and LNAV Cats C/D visibility ⅜ mile, increase Circling Cat C visibility ¼ mile, and Circling Cat D visibility ½ mile. Baro-VNAV and VDP NA when using Marion altimeter setting. Helicopter visibility reduction below ⅜ SM NA.

MISSED APPROACH:
Climb to 3000 direct BATGE and hold.

AWOS-3P 119.475	MERIDIAN APP CON* 121.275 348.7	UNICOM 122.8 (CTAF) 0
---------------------------	---	---------------------------------



ELEV 112	TDZE 107
----------	----------



3000		BATGE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.25/TCH 43).		4 NM
*LNAV only.			CUBNO Holding Pattern		
RW22		RIPNE 2NM to RW22	AFPAD 2000	045° → 3000	
*1 NM to RW22				← 225°	
*780			2000	GP 3.00°	
1 NM		1 NM	3.8 NM	TCH 40	
CATEGORY		A	B	C	D
LPV DA		369-7/8		262 (300-7/8)	
LNAV/VNAV DA		385-7/8		278 (300-7/8)	
LNAV MDA		480-1		373 (400-1)	
CIRCLING		720-1 608 (700-1)		720-1 3/4 608 (700-1 3/4)	
				780-2 668 (700-2)	

SE-4, 30 NOV 2023 to 28 DEC 2023

SE-4, 30 NOV 2023 to 28 DEC 2023