

ILS or LOC RWY 22

LOC I-CVS 109.7	APCH CRS 218°	Rwy Idg 10,003 TDZE 4295 Arprt Elev 4295	AL-512 [USAF]	CANNON AFB (KCVS)
---------------------------	-------------------------	---	---------------	-------------------

▼ * When ALS inop, increase RVR to 40 and vis to ¾ miles.
 ** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile,
 CAT CDE vis to 1 ¼ miles.

ALS-F-1

† MISSED APPROACH: Climb to 6000 out CVS TACAN R-220 to 6 DME (JEBES) then turn left climbing to 7000 intercept CVS R-193 to 12 DME (CLINK) and hold.

ATIS 119.1 269.9	CANNON APP CON 118.425 352.1	CANNON TOWER 120.4 270.25	GND CON 121.9 275.8	CLNC DEL 120.2 293.225
----------------------------	--	-------------------------------------	-------------------------------	----------------------------------

CAUTION:
 1. ILS Rwy 22 Height Group 4 WCH 19 feet.

† Missed approach requires use of RNAV or ATC RADAR monitoring.

EMERG SAFE ALT 100 NM 8000

6000 CVS R-220	JEBES CVS R-220 6	7000	CLINK CVS R-193 12	VGSI and ILS glidepath not coincident (VGSI Angle 3.00°/TCH 38).
-------------------	-----------------------------	------	------------------------------	--

TACAN

LOC MAP **1.2**

HEDOB R-003
12

7000

OPKUE **5.1**

218°

5600

ARC **12**

GS 3.00° TCH 44

ELEV 4295	TDZE 4295
-----------	-----------

CATEGORY	A	B	C	D	E
S-ILS 22*	4495/24		200	(200-½)	
S-LOC 22**	4720/24 425 (500-½)		4720/40 425 (500-¾)		
C CIRCLING	4840-1 545 (600-1)		4860-1 ½	5000-2 ¼	5020-2 ½
			565 (600-1 ½)	705 (800-2 ¼)	725 (800-2 ½)

FAF to MAP 4 NM					
Knots	60	90	120	150	180
Min:Sec	4:00	2:40	2:00	1:36	1:20