

VORTAC ACY	APP CRS	Rwy ldg
117.15	133°	10000
Chan 118 (Y)	TDZE 75	Apt Elev 75

VOR RWY 13

ATLANTIC CITY INTL (ACY)

ASR

For inoperative MALSR, increase S-13 Cat D visibility to RVR 6000 and Cat E to 1½.

MALSR

A5

MISSED APPROACH: Climbing left turn to 2000 via ACY R-090 to SMITS INT/11 DME and hold.

ATIS	ATLANTIC CITY APP CON	ATLANTIC CITY TOWER	GND CON	CLNC DEL
125.725 316.15	124.6 327.125	120.3 239.0	121.9 284.6	127.85 353.775

One Minute Holding Pattern

1900

313°

133°

BURDK INT ACY 5.4 RADAR

1600

133°

3.04°

TCH 58

3.4 NM

1.1 NM

2000

ACY R-090

SMITS

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 71).

3.04°

TCH 58

CATEGORY	A	B	C	D	E
S-13	480/24 405 (500-½)		480/40 405 (500-¾)	480/50 405 (500-1)	
CIRCLING	540-1 465 (500-1)	600-1 525 (600-1)	620-1½ 545 (600-1½)	640-2 565 (600-2)	760-2½ 685 (700-2½)

ELEV 75

D

TDZE 75

TDZ/CL Rwy 13

HIRL Rwys 4-22 and 13-31

REIL Rwy 31

FAF to MAP 4.5 NM

Knots	60	90	120	150	180
Min:Sec	4:30	3:00	2:15	1:48	1:30

ATLANTIC CITY, NEW JERSEY
Amdt 4C 09SEP21

39°27'N-74°35'W

ATLANTIC CITY INTL (ACY)
VOR RWY 13