

WAAS CH 69316 W17A	APP CRS 180°	Rwy Idg TDZE Apt Elev	6003 213 213
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 17

WEST MEMPHIS MUNI (A WM)

RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). When local altimeter setting not received, use Memphis Intl altimeter setting and increase LPV DA to 513 feet, LNAV/VNAV DA to 644 feet and all visibilities ¼ SM; increase all MDAs 60 feet and increase visibility LNAV Cat C and Circling Cat C and D ¼ SM. Baro-VNAV and VDP NA when using Memphis Intl altimeter setting.

MALS R

MISSED APPROACH: Climb to 2100 direct USUPE and hold.

ASOS
118.175

MEMPHIS APP CON
119.1 291.6

CLNC DEL
121.7

UNICOM
123.05 (CTAF) **0**

ELEV **213**

TDZE **213**

180° to RWY 17

35

MIRL Rwy 17-35

REIL Rwy 35

2100

USUPE

*LNAV only.

*1 NM to RWY 17

RWY 17

HEDIM

IMUDE

4 NM Holding Pattern

2500

GP 3.00° TCH 51

CATEGORY	A	B	C	D
LPV DA		463-½	250 (300-½)	
LNAV/VNAV DA		594-¾	381 (400-¾)	
LNAV MDA	600-½	387 (400-½)	600-⅝ 387 (400-⅝)	600-1 387 (400-1)
CIRCLING	640-1 427 (500-1)	740-1 527 (600-1)	800-1½ 587 (600-1½)	920-2¼ 707 (800-2¼)

WEST MEMPHIS, ARKANSAS

Orig-B 30DEC21

35°08'N-90°14'W

WEST MEMPHIS MUNI (A WM)

RNAV (GPS) RWY 17