

WAAS CH 90519 W04A	APP CRS 040°	Rwy Idg TDZE 1990 Apt Elev 1999
--	------------------------	---



RNAV (GPS) RWY 4

HAYS RGNL (HYS)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 45°C (113°F).
DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Russell altimeter setting: increase LPV DA to 2309 feet and visibility all Cats ¼ SM; increase LNAV/VNAV DA to 2347 feet and visibility all Cats ¼ SM; increase all MDA 80 feet and visibility LNAV Cat C and Circling Cat C and D ¼ SM. Circling NA for Cat D northwest of Rwy 4 and west of Rwy 16. Baro-VNAV NA when using Russell altimeter setting.

MISSED APPROACH:
Climb to 4000 direct
HOSNI and hold.

AWOS-3PT 125.525	KANSAS CITY CENTER 124.4 322.4	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



4 NM Holding Pattern		UTUCO	WOVEP	4000	HOSNI
4000		220°	040°	3700	
GP 3.00°					
TCH 40					
		6.1 NM	3.3 NM	1.9 NM	
CATEGORY	A	B	C	D	
LPV DA	2240-1		250 (300-1)		
LNAV/VNAV DA	2278-1		288 (300-1)		
LNAV MDA	2420-1	430 (500-1)	2420-1½ 430 (500-1½)	2420-1½ 430 (500-1½)	
CIRCLING	2480-1	481 (500-1)	2560-1½ 561 (600-1½)	2680-2½ 681 (700-2½)	